

(12) **INTERNATIONAL APPLICATION PUBLISHED UNDER  
THE PATENT COOPERATION TREATY (PCT)**

(19) World Intellectual Property Organization  
International Bureau

[WIPO]

[Bar Code]

(43) International Publication Date  
October 20, 2005 (10/20/2005)

**PCT**

(10) International Publication Number  
**WO 2005/096863 A1**

(51) International Patent Classification<sup>7</sup>: **A44B 18/00**

(74) Representative: **BARTELS UND PARTNER**; Lange  
Strasse 51, 70174 Stuttgart (DE).

(21) International Application No.: **PCT/EP2005/002216**

(22) International Filing Date:  
March 3, 2005 (03/03/2005)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL,  
AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE,  
EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN,  
IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI,  
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE,  
SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG,  
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Language in which the international application was  
originally filed: **German**

(26) Language in which the international application is  
published: **German**

(30) Priority Data:  
10 2004 015 321.3 March 30, 2004 (03/30/2004) DE


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW,  
GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TY, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,  
TM), European Patent (AT, BE, GB, CH, CY, CZ, DE,  
DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU,

(72) Inventor; and

(75) Inventor/Applicant (*U.S. only*): **POULAKIS, Kon-  
stantinos** [DE/DE]; Länderstrasse 2, 71157 Hildriz-  
hausen (DE).

[continued on next page]

(54) Title: **HOOK AND LOOP CONNECTOR PIECE**



(57) Abstract: The invention relates to a hook and loop connector piece, comprising a support band (10) with hooking elements (12) arranged on one side thereof and at least one cover strip (20), forming at least one free lateral edge region (21) extending over the corresponding lateral edge (33) of the support band (10), whereby the respective free lateral edge region (21) of the respective cover strip (20) may be folded over itself, along a fold line (29), running in the longitudinal direction such that the terminal edge (31) of the respective free lateral edge region (21) of the cover strip (20) is turned towards the corresponding lateral edge (33) of the support band (10), whereby, on the side of the hook and loop connector piece away from the hooking elements (12), a connector means (36) for a moulded foam is provided, said connector means (36) being embodied as a number of projecting separate rods (38) which perform the adhesion of the foam without additional projections.

[Fortsetzung auf der nächsten Seite]

WO 2005/096863 A1

MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*Reference is made for an explanation of the two-letter codes and the other abbreviations to the Guidance Notes on Codes and Abbreviations in the front section of each regular PCT Gazette edition.*

**Published:**

— *With International Search Report.*